

3 MP Fixed Dome IP-Camera 2.8~12mm Motorized GD-CI-AT3637V

GRUNDIG



Type: Fixed Dome - IP - Camera

Item Code: GD-CI-AT3637V


EAN CODE: 4260573060122

PREMIUM

The PREMIUM product line offers versatile solutions with unique and unparalleled features.

Highlights

H.265+



H.265pro+ utilizes the standard H.265/High Efficiency Video Coding (HEVC) format, but boasts advanced technologies that enable it to substantially reduce the necessary transmission bandwidth and storage capacity for maximum efficiency.

Features

- 3 Megapixel IP Camera with real time video streaming
- Audio Communication & Alarm Input / Output
- 3 Axis Gimbal for wall and ceiling mount
- Motorized Varifocal Lens: $f = 2.8 - 12 \text{ mm}$
- Split dome cover camera removes the IR reflection problem from the dust or moisture on the dome cover
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 30m

3 MP Fixed Dome IP-Camera 2.8~12mm Motorized

GD-CI-AT3637V

GRUNDIG

Specifications GD-CI-AT3637V

Camera

Image Sensor:	1/2.8" progressive Scan CMOS
Video Resolution:	2048 × 1536
Sensitivity Colour:	0.005 Lux @ F1.2 (AGC ON)
Sensitivity B/W:	0.0005 Lux @ (F1.2 (AGC ON)) , 0.0007 Lux @ (F1.4 (AGC ON)) , 0 Lux with IR
Shutter Speed:	1 ~ 1/100,000 s
Slow Shutter:	Support
White Balance:	Manual, AWB1, AWB2, Locked WB, Fluorescent lamp, Incandescent lamp, Warm light, Natural light

Lens

Lens Focal Length:	2.8 ~ 12 mm motorized, autofocus
Iris F-Number:	F1.4
Lens Mount:	Ø14
Lens Drive Type:	DC Auto Iris

Illuminator

Max. IR Distance:	Up to 30 m
Wavelength:	850 nm

Video

Col/B&W:	On, Off, Auto, IR-cut filter removable (ICR)
Wide Dynamic Range:	120 dB
Image Enhancement:	BLC, 3D DNR, Defog, EIS, HLC
Image Settings:	Rotate mode, Saturation, Brightness, Contrast, Sharpness and white balance adjustable by client software or web browser
Day/Night Switch:	Support auto, scheduled, day, night, triggered by alarm in

Audio

Audio Compression:	G.711ulaw/G.711alaw, G.722.1, G.726, MP2L2, PCM
Audio Bit Rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)
Environment Noise Filtering:	yes

Network

Users:	3 Levels: Administrator, Operator and User
Number of Clients:	Up to 20 simultaneously
Functions:	One-key reset, anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP-address filter
Video Compression:	Main Stream: H.264, H.264+, H.265, H.265+ Sub-Stream: H.264, H.265, MJPEG Third Stream: H.264, H.265
Region of Interest:	Support four fixed region for each stream, and dynamic face tracking
H.264 code profile:	Baseline Profile / Main Profile / High Profile
Bit Rate:	32Kbps ~ 16Mbps, adjustable
SD Memory:	Micro SD/SDHC/SDXC card slot with ANR (up to 128G), NAS (Support NFS, SMB/CIFS)
Network Protocol:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SNMP, SMTP, IGMP, 802.1X, QoS, IPv4/IPv6, UDP, PPPoE, Bonjour, SRTP, SFTP, SSL/TLS

I/O Interface

Video Outputs:	1 Test Monitor output (CVBS, 1 Vpp). Adapter cable with female BNC connector included.
----------------	--

3 MP Fixed Dome IP-Camera 2.8~12mm Motorized

GD-CI-AT3637V

GRUNDIG

I/O Interface

Audio Input/Output:	1-ch audio input and 1-ch audio output
Alarm Input/Output:	2 inputs, 2 outputs (up to 24 VDC 1 A or 110 VAC 500mA)

Intelligent Functions

Intrusion Detection:	Enter and loiter in a pre-defined virtual region, up to 4 pre-defined virtual regions supported
Line Crossing:	Cross a pre-defined virtual line, up to 4 pre-defined virtual lines supported
Region Entrance:	Enter a pre-defined virtual region from the outside place
Region Exiting:	Exit from a pre-defined virtual region
Unattended Baggage:	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
Object Removal:	Objects removed from the pre-defined region, such as the exhibits on display
Face Detection:	Human face appears in the image can be detected and trigger event action
Tamper Protection:	Detection of scene change, defocus, sudden audio increase/decrease or audio loss.
Event Source:	Video tampering, network disconnected, IP address conflicted, HDD full, HDD error, illegal login, motion detection
Event Action:	Recording: Pre-event, post-event memory card and/or network storage. Picture upload: FTP, HTTP and NAS. Trigger E-mail notification: HTTP, ISAPI. Alarm output and notification to C-WERK VMS. Events are depending on schedule settings.

Approvals

Protection Rating:	IP66 (IEC 60529-2013)
Regulation:	CE, EAC, FCC, RoHS Compliant
Standard:	ONVIF (Profile S, Profile G), SDK/API

Environmental

Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	Less than 95%, non condensing


Electrical

Supply Voltage:	12 VDC, PoE (IEEE 802.3af)
Power Consumption:	Max. 10 W

Mechanical

Mount:	Pan: 0° to 355°, tilt: 0° to 70°, rotate: 0° to 355°, 3-Axis Adjustment
Weight:	1200 g (2.65 lb)


Accessories



GD-CW-VIEWER



GD-CW-FINDER



GD-SW-SCMS



GD-BR-AMP11

3 MP Fixed Dome IP-Camera 2.8~12mm Motorized
GD-CI-AT3637V

GRUNDIG



GD-BR-AMP02



GD-BR-AMP03



GD-BR-AMP05



GD-BR-AMW07