

GD-CI-BP2747P

2 MP PTZ Dome IP-Camera 32x Zoom ICR IR LED WDR H.265+



- Intelligent Video Analytics Function
- 32x motorized optical zoom with 16x digital zoom
- Privacy Zone Masking Function
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 200m (Detection)
- Supports 24 VAC & HI Power over Ethernet (PoE)

**PROFESSIONAL**

- Product Line Professional: These products cover most applications of modern video systems

Item Code: GD-CI-BP2747P

EAN CODE: 4260573062232

Specifications GD-CI-BP2747P

Camera

Image Sensor:	1/2.8" progressive Scan CMOS
Video Resolution:	1920 x 1080
Sensitivity Colour:	0.005 Lux @ F1.6 (AGC ON)
Sensitivity B/W:	0.001 Lux @ (F1.6, AGC ON)
Shutter Speed:	1 ~ 1/30,000 s
White Balance:	Auto, Manual, ATW, Indoor, Outdoor, Fluorescent light, Sodium light

Lens

Lens Focal Length:	4.8 ~ 153 mm motorized, autofocus
Iris F-Number:	F1.2 ~ F4.4
Focus Adjustment:	Auto, Manual
Optical Zoom Ratio:	32x
Digital Zoom:	16x
Field of View:	55.6° ~ 2.04° (horizontal), 32.4° ~ 1.14° (vertical), 63° ~ 2.34° (diagonal)

Illuminator

Max. IR Distance:	Up to 200m
Wavelength:	850 nm
IR angle:	Adjustable by zoom

Video

Col/B&W:	Auto, Color, Removable IR-Cut Filter (ICR)
Wide Dynamic Range:	120 dB
Image Enhancement:	BLC, 3D DNR, Defog, EIS, HLC, AGC, Regional Exposure, Regional Focus
Day/Night Switch:	Color, BW, Auto

Audio

Audio bit rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)
Audio detection:	Off, On

Network

Number of Clients:	Up to 20 simultaneously
Video Compression:	Main Stream: H.264, H.264+, H.265, H.265+ Sub-Stream: H.264, H.265, MJPEG Third Stream: H.264, H.265, MJPEG
H.264 code profile:	Baseline Profile / Main Profile / High Profile
Bit Rate:	32Kbps ~ 16Mbps
Scalable Video Coding (SVC):	supported
SD memory:	Micro SD/SDHC/SDXC card slot with ANR (up to 256G), NAS (Support NFS, SMB/CIFS)

Item Code: GD-CI-BP2747P

EAN CODE: 4260573062232

Network

Frame Rate:	Main Stream 50Hz: 50fps(1920 × 1080, 1280 × 960, 1280 × 720), 60Hz: 60fps (1920 × 1080, 1280 × 960, 1280 × 720) Sub Stream 50Hz: 25fps(704x576, 640x480, 352x288), 60Hz: 30fps (704x480, 640x480, 352x240) Third Stream 50Hz: 25fps(1920 × 1080, 1280 × 960, 1280 × 720, 704x576, 640x480, 352x288), 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704x480, 640x480, 352x240)
Network Protocol:	TCP/IP, IPv4, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour, UDP, PPPoE, SNMP
Cyber Security:	3 levels of user management: admin, operator, user, AES Encryption for Password Protection, Complicated Password, HTTPS (SSL) Login Authentication, Basic and digest authentication for HTTP/HTTPS, 802.1X authentication , (EAP-LEAP), 802.1X authentication (EAP-TLS), 802.1X authentication (EAP-MD5), Watermark, IP Adress Filter, WSSE and digest authentication for ONVIF, SNMP V2 , SNMP V3, TLS 1.0, TLS 1.1, TLS 1.2, TLS 1.2 with updated cipher suites including AES 256 encryption. Brute Force Delay Protection, Signed Firmware, Secure Boot by hardware check
Network Storage:	Micro SD, SDHC, SDXC card with ANR (up to 256G) , NAS (Support NFS, SMB, CIFS)

Pan Tilt Zoom

Number of Privacy Zones:	24 programmable zones
Number of Patrols:	8 patrols, up to 32 presets for each patrol
Number of Pattern:	4 pattern scans, record time over 10 minutes for each scan
Number of Preset:	300
Pan Speed:	Configurable, from 0.1°/sec to 160°/sec, Preset Speed: 240°/sec
Tilt Speed:	Configurable from 0.1°/sec to 120°/sec, Preset Speed: 200°/sec
Range Panning:	360° endless
Range Tilting:	-15° ~ 90° (auto flip) 210° total
Schedule:	Preset, Pattern Scan, Patrol Scan, Auto Scan, Tilt Scan, Random Scan, Frame Scan, Panorama Scan, Dome Reboot, Dome Adjust
Park Action:	Preset, Patrol, Pattern, Auto scan, Tilt scan, Random scan, Frame scan, Panorama scan
Preset Freezing:	Support
Proportional Zoom:	Rotation speed can be adjusted automatically according to zoom multiples
PTZ Status Display:	ON, OFF
Tracking Functions:	Manual Tracking, Auto Tracking, Event Tracking

I/O Interface

Network Interface:	1x 10, 100 Base T, TX HiPoE (RJ-45)
Alarm Input/Output:	2 inputs, 1 output (up to 12 VDC, 30 mA) , terminal block
Audio Input/Output:	1-ch audio input and 1-ch audio output

Intelligent Functions

Motion Detection:	On, Off
Tamper protection:	Scene change and defocus
Line Crossing Detection:	Cross a pre-defined virtual line
Intrusion Detection:	Enter and loiter in a pre-defined virtual region
Region Entrance:	Enter a pre-defined virtual region from the outside place
Region Exiting:	Exit from a pre-defined virtual region

Item Code: GD-CI-BP2747P

EAN CODE: 4260573062232

Intelligent Functions

Unattended Baggage:	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
Object Removal:	Objects removed from the pre-defined region, such as the exhibits on display
Face Detection:	Human face appears in the image can be detected and trigger event action. This feature is deactivated if 3rd stream or H.264+ or H.265+ is on.

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
Protection Rating:	IP66 (IEC 60529-2013), IK10 (IEC 62262:2002)
Standard:	ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

Environmental

Operating Temperature:	-40 °C ~ 65 °C (-40 °F ~ 149 °F)
Humidity:	Less than 95%, non condensing

Electrical

Surge Protection:	TVS 4000V Lightning Protection, Surge Protection and Voltage Transient Protection
Supply Voltage:	24 VAC, PoE+ (IEEE 802.3at)
Power Consumption:	Max. 40 W

Mechanical

Dimensions:	Ø 220 × 363 mm (Ø 8.66 × 13.91 inch)
Weight:	4685 g (10.33 lb)

Accessories:

GD-BR-AWJ03



GD-BR-AMC04



GD-BR-AML06

Item Code: GD-CI-BP2747P

EAN CODE: 4260573062232



GD-BR-AMP01



GD-BR-AMP04



GD-BR-AMP06



GD-BR-AMP07



GD-BR-AMA01



GD-BR-AMS01



GD-BR-AMW08



GD-BR-AMW10