2 MP Bullet HD-TVI Camera 3.6 mm

GD-CT-BC2116T

Type: Bullet - HD-Analogue - Camera
Item Code: GD-CT-BC2116T
EAN CODE: 4260573062720

ESSENTIAL

Our ESSENTIAL product line is designed to deliver high-quality performance, with basic features and impressive functions, making it perfect for smaller applications.

Essential Line

Many small to medium-sized systems are capable of operating without any specific requirements. Simply storing video sequences is often sufficient in the event of an incident, allowing for the course of events to be determined through recorded footage. GRUNDIG Security provides a comprehensive range of standard applications to meet these needs, including cameras that capture high-resolution images regardless of lighting conditions and recorders capable of storing video sequences for weeks or months, although privacy concerns may prevent this practice. The "Essential" product line offers high image quality, making it ideal for meeting basic requirements.

Features

- 2 Megapixel HD-TVI Camera with HD 1080P real time video
- 3 Axis Gimbal for wall and ceiling mount
- Smart IR Control
- Lens: f = 3.6 mm
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 20m
- Power Input DC12V

Specifications GD-CT-BC2116T

Camera	
Image Sensor:	2 Megapixel progressive scan CMOS
Pixels - Effective:	1920 (H) x 1080 (V)
Sensitivity Colour:	0.01 Lux @ F1.2 (AGC ON)
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/25 (1/30) ~ 1/50,000 s
White Balance:	Auto, Manual
Lens	
Lens Focal Length:	3.6 mm
Iris F-Number:	F2.0
Lens Mount:	M12
Field of View:	82.2°
Illuminator	
Max. IR Distance:	Up to 20 m
Wavelength:	850 nm
Video	
Video Standard:	PAL, NTSC
Col/B&W:	Auto , Color , B&W, IR-cut filter removable (ICR)
Wide Dynamic Range:	Digital WDR
Image Enhancement:	BLC, 2D DNR, Anti-Flicker, Mirror, AGC
S/N Ratio:	>62 dB
Frame Rate (Max@Resolution):	PAL: 1080p@25fps NTSC: 1080p@30fps
General	
OSD (On Screen Display):	English
Coaxial control:	Control over Coax (CoC)
I/O Interface	
Video Outputs:	1x HD-TVI (BNC)
Approvals	
Protection Rating:	IP66 (IEC 60529-2013)
Regulation:	CE, EAC, FCC, RoHS Compliant
Environmental	
Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	Less than 95%, non condensing
Electrical	
Supply Voltage:	12 VDC ±10%
Power Consumption:	Max. 4 W
Mechanical	
Mount:	Pan: 0° to 360°, tilt: 0° to 90°, rotation: 0° to 360°, 3-Axis Adjustment
Dimensions:	150 x 55 x 58 mm (5.9 x 2.17 x 2.28 inch)
Weight:	150 g (0.33 lb)

Packaging	
Package Dimensions:	158 x 104 x 80 mm (6.2 x 4.1 x 3.1 inch)
Package Weight:	300 g (0.7 lbs)
Packaging Unit:	40
Bulk Package Dimensions:	535 x 352 x 335 mm (21.1 x 13.9 x 13.2 inch)
Bulk Package Weight:	12500 g (27.6 lbs)

Accessories

GD-AC-VB01

GD-BR-AJX05