

2 MP HD-TVI Camera 2.8~12mm Motorized GD-CT-CP2837T

GRUNDIG



Type: Bullet - HD-Analogue - Camera

Item Code: GD-CT-CP2837T

EAN CODE: 4260573065172

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.

Highlights

Ultra Low Light



Designed for unparalleled performance in low-light environments, this camera incorporates advanced image processing and a high-capacity image sensor, ensuring exceptional image quality even in ultra-low light conditions.

Features

- 2 Megapixel HD-TVI Camera with HD 1080P real time video
- Ultra Low Light CMOS Sensor, Smart-IR Control
- Smart Illumination with White Light and IR Light
- Support Dual Power PoC and DC12V
- Motorized Varifocal Lens: $f = 2.8 - 12 \text{ mm}$
- 3 Axis Gimbal for wall and ceiling mount
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 60m

Specifications GD-CT-CP2837T

Camera

Image Sensor:	2 Megapixel progressive scan CMOS
Pixels - Effective:	1920 (H) x 1080 (V)
Sensitivity Colour:	0.0005 Lux
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/25 (1/30) ~ 1/50,000 s
Slow Shutter:	Support
White Balance:	Auto , Manual

Lens

Lens Focal Length:	2.8 ~ 12 mm motorized
Lens Mount:	Ø14
Field of View:	106° ~ 32° (horizontal), 56° ~ 18° (vertical), 127° ~ 37° (diagonal)

Illuminator

Max. IR Distance:	Up to 60 m
White Light Distance:	Up to 60 m

Video

Video Standard:	PAL, NTSC
Col/B&W:	Auto , Color , B&W, IR-cut filter removable (ICR)
Wide Dynamic Range:	130 dB
Image Enhancement:	BLC, 3D DNR, HLC, Anti-Flicker, Mirror, AGC, WDR, Brightness, Sharpness, Smart-IR
Frame Rate (Max@Resolution):	PAL: 1080p@25fps NTSC: 1080p@30fps
Privacy zones:	4 zones, rectangle

General

OSD (On Screen Display):	English
Coaxial control:	Coaxitron®, CCVC

I/O Interface

Video Outputs:	1x HD-TVI (BNC)
Audio Input/Output:	Built-in microphone

Intelligent Functions

Motion Detection:	4 programmable zones
-------------------	----------------------

Approvals

Protection Rating:	IP67 (IEC 60529-2013)
Regulation:	CE, RoHS Compliant

Environmental

Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	Less than 90%, non condensing

Electrical

Supply Voltage:	12 VDC ±15%, PoC.at
Power Consumption:	Max. 8 W

Mechanical

Material:	Metal
-----------	-------

Mechanical

Mount:	Pan: 0° to 360°, tilt: 0° to 90°, rotation: 0° to 360°, 3-Axis Adjustment
Dimensions:	Ø 105 × 252 mm (Ø 4.1 × 9,9 inch)
Weight:	920 g (2.02 lb)

Packaging

Package Dimensions:	279 x 119 x 130 mm (11 x 4.7 x 5.1 inch)
Package Weight:	1000 g (2.2 lbs)
Packaging Unit:	12
Bulk Package Dimensions:	580 x 380 x 287 mm (22.8 x 15 x 11.3 inch)
Bulk Package Weight:	12500 g (27.6 lbs)

Accessories

GD-AC-VB02




GD-BR-AJX04



GD-BR-AMC03



GD-BR-AML01

Dimensions**Guarantee**

All cameras in the "SMART", "PRO" and "PREMIUM" product lines have an extended warranty period of 5 years on electronic parts, mechanical wear and tear on moving parts is not included. Please note our general delivery terms and conditions.