

## GD-HW-APCM420

4G LTE WIFI 4 port Lan Modul



- Dual SIM with 4G LTE
- Wireless Access Point with Hotspot functionality



### PROFESSIONAL

- Product Line Professional: These products cover most applications of modern video systems

Item Code: GD-HW-APCM420

EAN CODE: 4260573062577

## Specifications GD-HW-APCM420

### General

|                 |                                                                                     |
|-----------------|-------------------------------------------------------------------------------------|
| CPU:            | Atheros Wasp, MIPS 74Kc, 550 MHz                                                    |
| LED Indicators: | 1 x bi-colour connection status, 5 x connection strength, 4 x LAN status, 1 x Power |
| Memory:         | 16 MB Flash, 128 MB DDR2 Ram                                                        |

### Network

|                     |                                                                                                                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network Protocol:   | TCP/IP, ICMP, HTTP, HTTPS, DHCP, NTP, UPnP, SMTP, IGMP, IPv6, UDP, SSH, PPP, MQTT, SSL v3, TLS ARP, Telnet, VRRP                                                                                            |
| Transmission Media: | Dual SIM 4G (LTE) Cat4 DL up to 150 Mbps, UL up to 50Mbps, DC-HSPA+, UMTS, TD-SCDMA, EDGE, GPRS<br>Wireless Access Point with Hotspot functionality<br>WAN automatic switch to available back up connection |

### I/O Interface

|                    |                                                                         |
|--------------------|-------------------------------------------------------------------------|
| Network Interface: | 4 RJ-45 10, 100, 1000Mbps self-adaptive Ethernet interface              |
| Inputs/Outputs:    | 1 x Digital Input, 1 x Digital Open Collector Output on power connector |

### Environmental

|                        |                                  |
|------------------------|----------------------------------|
| Operating Temperature: | -40 °C ~ 75 °C (-40 °F ~ 167 °F) |
|------------------------|----------------------------------|

### Electrical

|                 |                                |
|-----------------|--------------------------------|
| Supply Voltage: | 9 - 30 VDC, 4 pin DC connector |
|-----------------|--------------------------------|

### Mechanical

|             |                                            |
|-------------|--------------------------------------------|
| Dimensions: | 100 x 110 x 50 mm (3.9 x 4.33 x 1.97 inch) |
| Weight:     | 250 g (0.55 lb)                            |
| Material:   | Aluminium, Plastic                         |