



Type: Joystick Controller - System Keyboard - Hardware

Item Code: GD-KB-AC1420P

EAN CODE: 4260573065226

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.


Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Essential Line

Many small to medium-sized systems are capable of operating without any specific requirements. Simply storing video sequences is often sufficient in the event of an incident, allowing for the course of events to be determined through recorded footage. GRUNDIG Security provides a comprehensive range of standard applications to meet these needs, including cameras that capture high-resolution images regardless of lighting conditions and recorders capable of storing video sequences for weeks or months, although privacy concerns may prevent this practice. The "Essential" product line offers high image quality, making it ideal for meeting basic requirements.

Many small to medium-sized systems are capable of operating without any specific requirements. Simply storing video sequences is often sufficient in the event of an incident, allowing for the course of events to be determined through recorded footage. GRUNDIG Security provides a comprehensive range of standard applications to meet these needs, including cameras that capture high-resolution images regardless of lighting conditions and recorders capable of storing video sequences for weeks or months, although privacy concerns may prevent this practice. The "Essential" product line offers high image quality, making it ideal for meeting basic requirements.

Features

- Auto Protocol Search Function for easy installation
- Auto Protocol Search Function for easy installation
- Durable 3-axis PTZ joystick
- Control DVR and PTZ separately
- Control NVR, DVR and PTZ separately
- Durable 3-axis PTZ joystick

Specifications GD-KB-AC1420P

General

PTZ Control: 4-axis joystick, PTZ-, focus- & iris-control, setting and calling Presets, Patterns & Patrols, Auto-Scan, Auto-Pan, Wiper, AUX

PTZ Control: 3-axis Joystick, Pan, Tilt, Zoom, Focus, Preset, Sequence, Auto Pan

Network

Users: 1 user, 1 level

Users: 1 user, 1 level

I/O Interface

Serial Interface(s): USB 2.0, DirectX

Serial Interface(s): USB 2.0, DirectX

Environmental

Operating Temperature: -10°C ~ +55°C (+14°F ~ + 131°F)

Operating Temperature: -10°C ~ +55°C (+14°F ~ + 131°F)

Humidity: Less than 90%, non condensing

Humidity: Less than 90%, non condensing

Electrical

Supply Voltage: 12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included

Supply Voltage: 12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included

Supply Voltage: 5 VDC by USB port

Power Consumption: Max. 5 W

Power Consumption: Max. 15 W

Mechanical

Dimensions: 167 x 116 x 178 (6.6 x 4.6 x 7.0 inch)

Weight: 1650 g (3.3 lb)

Weight: 520 g (1.15 lb)

Packaging

Package Dimensions: 337 x 200 x 295 mm (13.3 x 7.9 x 11.6 inch)

Package Weight: 800 g (1.8 lbs)