

54,6 cm (21.5") Monitor

GD-ML-AC2220HD

GRUNDIG



Type: Full HD - LCD/TFT - Monitor

Item Code: GD-ML-AC2220HD

EAN CODE: 4260573064472

ESSENTIAL

Our ESSENTIAL product line is designed to deliver high-quality performance, with basic features and impressive functions, making it perfect for smaller applications.

Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Features

- Designed for professional 24/7 usage
- Displays a full, flat 21,5" (54.6 cm) diagonal image
- Accepts either HD-TVI, CVI, AHD or analog signals
- LED Backpanel illumination
- 1 HDMI, 2 BNC Input

Specifications GD-ML-AC2220HD

Display

LCD Panel size:	54.6 cm (21, 5") Diagonal AM-TFT LED Backlight
Pixels - Total:	1920 (H) x 1080 (V)
Aspect Ratio:	16 : 9
Viewing Angle:	178° (H) ~ 178° (V)

Video

Video Inputs:	1x HDMI, 2x BNC
Video Standard:	PAL, NTSC
Brightness:	250 cd, m ²
Contrast Ratio:	1000:1
Number of Colours:	16.7 million
Response Time:	5 ms

General

OSD (On Screen Display):	Yes, multi language
Accessories included:	Power Adapter and HDMI cable

I/O Interface

Video Outputs:	2x HD-analog (BNC)
----------------	--------------------

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	>50,000 hours

Environmental

Operating Temperature:	0 °C ~ +40 °C
Humidity:	Less than 90%, non condensing

Electrical

Supply Voltage:	12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included
Power Consumption:	Max. 21 W

Mechanical

Material:	Robust Plastic
Vesa Mount:	75 x 75 mm
Dimensions:	580 x 440 x 120 mm (22.8 x 17.3 x 4.7 inch)
Weight:	3800 g (8.4 lb)