

GD-ML-AP1031SD

25.6 cm (10.1) LCD/TFT Monitor LED 16:9 Protection Glass



- Metal cabinet
- Displays a full, flat 10.1" (25.6cm) diagonal image
- High Contrast Ratio
- Scratch protection glass with anti-reflection coating



PROFESSIONAL

- Product Line PROFESSIONAL: These products cover most applications of modern video systems

Specifications GD-ML-AP1031SD

Display

LCD Panel size:	25.6 cm (10.1") Diagonal AM-TFT LED Backlight
Pixels - Total:	1280 (H) x 800 (V)
Pixel Pitch:	0.192 mm (H) x 0.192 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	160° (H) ~ 160° (V)

Video

Video Inputs:	1x Composite, BNC looped, 1x VGA, 1x HDMI
Video Standard:	PAL, NTSC
Brightness:	350 cd, m ²
Contrast Ratio:	800:1
Number of Colours:	262K
Response Time:	12 ms

General

Speakers:	yes
OSD (On Screen Display):	Yes, multi language
Accessories included:	Stand, power adapter, HDMI cable and remote control

I/O Interface

Video Outputs:	1 Vpp, BNC
Audio Inputs:	1x 3.5mm jack (Line) , 1x HDMI

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 50,000 hours

Environmental

Operating Temperature:	0 °C ~ +40 °C
Humidity:	Less than 90%, non condensing

Electrical

Supply Voltage:	12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included
Power Consumption:	Max. 12 W

Mechanical

Material:	Metal
Display protection:	Tempered acryl glass with anti-reflection coating
Vesa Mount:	75 x 75 mm
Dimensions:	185 x 250 x 38 mm (7,3 x 9,8 x 1,5 inch)
Weight:	1400 g (3.09 lb)

Item Code: GD-ML-AP1031SD

EAN CODE: 4260573060597