

GD-ML-AP2431HD

61 cm (23.6") LCD/TFT Monitor LED 16:9 with Protection Glass



- Displays a full, flat 23.6" (61 cm) diagonal image
- Designed for professional 24/7 usage
- LED Backpanel illumination
- Rack mount 19"
- Including IR Remote Control
- Scratch protection glass with anti-reflection coating



PROFESSIONAL

- Product Line Professional: These products cover most applications of modern video systems

Item Code: GD-ML-AP2431HD

EAN CODE: 4260573060634

® Abetechs GmbH (Grundig Security), Düsseldorf, Germany

grundig-security.com

Specifications GD-ML-AP2431HD

Monitor

LCD Panel size:	61 cm (23.6") Diagonal AM-TFT LED Backlight
Pixels - Total:	1920 (H) x 1080 (V)
Pixel Pitch:	0.248 mm (H) x 0.248 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	170° (H) ~ 170° (V)

Video

Video Inputs:	1x Composite, BNC, 1x VGA, 1x HDMI
Video Standard:	PAL, NTSC
Brightness:	250 cd, m ²
Contrast Ratio:	1000:1
Number of Colours:	16.7 million
Response Time:	5 ms

General

Speakers:	2 x 2.5 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Power adapter, HDMI cable and remote control

I/O Interface

Audio Inputs:	2 CH (1xHDMI, 1xMiniJack Connector)
Video Outputs:	1x CVBS (1 Vcc) BNC

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 100,000 hours

Environmental

Operating Temperature:	0 °C ~ +40 °C
Humidity:	Less than 90%, non condensing

Electrical

Supply Voltage:	12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included
Power Consumption:	Max. 25 W

Mechanical

Material:	Plastic
Display protection:	Tempered acryl glass with anti-reflection coating
Vesa Mount:	100 x 100 mm
Dimensions:	440 x 570 x 190 mm (17,3 x 22,4 x 7,5 inch)
Weight:	5200 g (11.5 lb)

Item Code: GD-ML-AP2431HD

EAN CODE: 4260573060634