GD-ML-BP2840UHD

71 cm (28") 4K UHD LCD/TFT Monitor

- Designed for professional 24/7 usage
- Ultra High Definition (UHD) TFT-LCD monitor
- LED Backpanel illumination
- Built-in Speaker

PROFESSIONAL

- Product Line PROFESSIONAL: These products cover most applications of modern video systems

Item Code: GD-ML-BP2840UHD

EAN CODE: 4260573064236

Specifications GD-ML-BP2840UHD

Display	
LCD Panel size:	71 cm (28") Diagonal AM-TFT LED Backlight
Pixels - Total:	3840 (H) x 2160 (V)
Pixel Pitch:	0.2715 mm (H) x 0.2715 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	170° (H) ~ 160° (V)
Video	
Video Inputs:	1x Display Port, 3x HDMI
Video Standard:	PAL, NTSC, SECAM
Brightness:	300 cd, m²
Contrast Ratio:	1000:1
Number of Colours:	1073 G
Response Time:	1.5 ms
General	
Speakers:	2 x 5 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Stand, power cable, HDMI cable and remote control
I/O Interface	
Audio Inputs:	1x HDMI
Approvals	
Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 100,000 hours
Environmental	
Operating Temperature:	0 °C ~ +50 °C
Humidity:	Less than 90%, non condensing
Electrical	
Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. 25 W
Mechanical	
Material:	Robust Plastic
Vesa Mount:	100 x 100 mm
Dimensions:	660 × 380 × 50 mm
Weight:	4700 g (10.3lb)

Item Code: GD-ML-BP2840UHD

EAN CODE: 4260573064236