

GD-ML-BP3230HD

81 cm (32") LCD/TFT Monitor LED 16:9



- Designed for professional 24/7 usage
- Displays a full, flat 32" (81cm) diagonal image
- Including IR Remote Control
- LED Backpanel illumination



PROFESSIONAL

- Product Line Professional: These products cover most applications of modern video systems

Item Code: GD-ML-BP3230HD

EAN CODE: 4260573063109

Specifications GD-ML-BP3230HD

Display

LCD Panel size:	81.3 cm (32") Diagonal AM-TFT LED Backlight
Pixels - Total:	1920 (H) x 1080 (V)
Pixel Pitch:	0.36375 mm (H) x 0.36375 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	178° (H) ~ 178° (V)

Video

Video Inputs:	1x Composite, BNC looped, 1x VGA, 1x HDMI
Video Standard:	PAL, NTSC
Brightness:	300 cd, m ²
Contrast Ratio:	1000:1
Number of Colours:	16.7 million
Response Time:	5 ms

General

Speakers:	2 x 2.5 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Stand, power cable, HDMI cable and remote control

I/O Interface

Audio Inputs:	1-ch, RCA (2.0 Vp-p, 1kΩ)
---------------	---------------------------

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 50,000 hours

Environmental

Operating Temperature:	0 °C ~ +45 °C
Humidity:	Less than 90%, non condensing

Electrical

Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. 60W

Mechanical

Material:	Robust Plastic
Vesa Mount:	100 x 100 mm
Dimensions:	730 x 431 x 94 mm
Weight:	5100 g