

81 cm (32") Monitor

GD-ML-BP3230HD

GRUNDIG



Type: Full HD - LCD/TFT - Monitor

Item Code: GD-ML-BP3230HD

EAN CODE: 4260573063109

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.

Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Features

- Designed for professional 24/7 usage
- Displays a full, flat 32" (81cm) diagonal image
- Including IR Remote Control
- LED Backpanel illumination

Specifications GD-ML-BP3230HD

Display

LCD Panel size:	81.3 cm (32") Diagonal AM-TFT LED Backlight
Pixels - Total:	1920 (H) x 1080 (V)
Pixel Pitch:	0.36375 mm (H) x 0.36375 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	178° (H) ~ 178° (V)

Video

Video Inputs:	1x Composite, BNC looped, 1x VGA, 1x HDMI
Video Standard:	PAL, NTSC
Brightness:	300 cd, m ²
Contrast Ratio:	1000:1
Number of Colours:	16.7 million
Response Time:	5 ms

General

Speakers:	2 x 2.5 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Stand, power cable, HDMI cable and remote control

I/O Interface

Audio Inputs:	1-ch, RCA (2.0 Vp-p, 1kΩ)
---------------	---------------------------

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 50,000 hours

Environmental

Operating Temperature:	0 °C ~ +45 °C
Humidity:	Less than 90%, non condensing

Electrical

Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. 60W

Mechanical

Material:	Robust Plastic
Vesa Mount:	100 x 100 mm
Dimensions:	730 x 431 x 94 mm
Weight:	5100 g

Packaging

Packaging Unit:	1
-----------------	---