# **GD-ML-DP4340UHD**









Type: 4K - LCD/TFT - Monitor Item Code: GD-ML-DP4340UHD EAN CODE: 4260573065790

### **PROFESSIONAL**

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.

## **Highlights**

#### **Continuous operation**



This Grundig Security device is capable of operating 24/7 continuously on any day.

#### **Features**

- Designed for professional 24/7 usage
- Ultra High Definition (UHD) TFT-LCD monitor

- Displays a full, flat 43" (109cm) diagonal image
- LED Backpanel illumination

# GD-ML-DP4340UHD



### **Specifications GD-ML-DP4340UHD**

Display

LCD Panel size: 109 cm (43") Diagonal AM-TFT LED Backlight

Pixels - Total: 3840 (H) x 2160 (V)

Pixel Pitch: 0.2451 mm (H) x 0.2451 mm (V)

Aspect Ratio: 16:9

Viewing Angle: 178° (H) ~ 178° (V)

Video

Video Inputs: 3x HDMI, 1x Display Port

Video Standard:PAL, NTSCBrightness:350 cd, m²Contrast Ratio:1000:1Number of Colours:1073 GResponse Time:5 ms

General

Speakers: 2 x 2.5 W

OSD (On Screen Display): Yes, multi language

Accessories included: Stand, power adapter, HDMI cable and remote control

I/O Interface

Audio Outputs: 1-ch, RCA

**Approvals** 

Regulation: CE, EAC, FCC, RoHS Compliant

MTBF at 25° C: >50,000 hours

**Environmental** 

Operating Temperature: 0 °C ~ +40 °C

Humidity: Less than 90%, non condensing

**Electrical** 

Supply Voltage: 100 ~ 240 VAC, 50Hz / 60Hz

Power Consumption: ≤ 75 W

Mechanical

Material: Metal

Vesa Mount: 400 x 400 mm

Dimensions: 970 x 565 x 40 mm (38.2 x 22.3 x 1.6 inch)

Weight: 8800 g (19.4 lb)