GD-RT-BC3008N













Type: Standalone HDVR - HD-Analogue - Recorder

Item Code: GD-RT-BC3008N EAN CODE: 4260573062775

ESSENTIAL

Our ESSENTIAL product line is designed to deliver high-quality performance, with basic features and impressive functions, making it perfect for smaller applications.

Highlights

Smartphone App



The mobile application was developed to facilitate operators in effectively controlling and managing video systems remotely, at any time. It allows for live image viewing, playback of recorded video data, and receipt of remote notifications.



Object Classification

This technology employs a highly advanced deep learning algorithm that can discern whether the alarm was triggered by a human, a vehicle or some other object.

Essential Line

Many small to medium-sized systems are capable of operating without any specific requirements. Simply storing video sequences is often sufficient in the event of an incident, allowing for the course of events to be determined through recorded footage. GRUNDIG Security provides a comprehensive range of standard applications to meet these needs, including cameras that capture high-resolution images regardless of lighting conditions and recorders capable of storing video sequences for weeks or months, although privacy concerns may prevent this practice. The "Essential" product line offers high image quality, making it ideal for meeting basic requirements.

Features

- Many intelligent functions: deep learning distinguishing between human and vehicles, face detection and capture, line crossing and intrusion alarm
- Auto detects HD-TVI, CVI, AHD or analog cameras
- Various recording features (schedule, motion, alarm)
- 10 recording tracks: Up to 2 IP channels can be used in addition to the analog channels. In the IP Enhance mode, up to 12 IP channels can be used as the analog channels are no longer available.
- Multiplex (Live/Playback, Recording, Backup, Networking)
- Integration of third-party cloud storage (Dropbox / Google Drive / Microsoft OneDrive)

GD-RT-BC3008N



Specifications GD-RT-BC3008N

Video

Video Inputs: 8-ch, BNC interface $(1.0 \text{ Vp-p}, 75 \Omega)$, supporting coaxitron connection

IP Inputs: 4 (12 IP enhance mode) up to 6 MP

HD-TVI Input: 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25

Note: The 3 MP signal input is only available for channel 1 of GD-RT-AC3004N, of channel 1/2 of

GD-RT-AC3008N and for channel 1/2/3/4 of GD-RT-AC3016N

AHD Input: 4 MP, 1080p25, 1080p30, 720p25, 720p30 CVI Input: 4 MP, 1080p25, 1080p30, 720p25, 720p30

CVBS Input: PAL, NTSC

Recording / Playback

Recording Bandwidth: 96 Mbps

Recording Resolution: 4 MP, 3 MP, 1080p, 720p, WD1, 4CIF (when 1080P lite not enabled)

Recording Mode: Continuous, Event Alarm, Motion, Video Loss, Schedule

Search Mode: Date, Time, Event Alarm, Motion, Search Backup, Quick search by object or event type

Playback: Synchronised playback of max. 8 cameras

Frame Rate(R): Main Stream (when 1080p Lite mode not enabled):

For 3 MP stream access: 3 MP, 1080p, 720p, VGA, WD1, 4CIF, CIF@15fps

For 1080p stream access: 1080p, 720p@15fps, VGA, WD1, 4CIF, CIF@25fps (P), 30fps (N)

For 720p stream access: 720p, VGA, WD1, 4CIF, CIF@25fps (P), 30fps (N)

When 1080p Lite mode enabled: 3 MP@15fps

1080p lite, 720p lite, VGA, WD1, 4CIF, CIF@25fps (P), 30fps (N) Sub-stream: WD1, 4CIF@12fps, CIF@25fps (P), 30fps (N)

Audio

Audio Compression: G.711

General

External Backup: USB HDD, USB Memory, USB DVD-R, Network

Max. Storage Capacity: Up to 10 TB capacity for each HDD PTZ Control: Pan, Tilt, Zoom, Preset set and call

Network

Video Compression: H.264, H.264+, H.265, H.265pro, H.265pro+

Network Protocol: TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF

Cyber Security: 3 levels of user management: admin, operator, user, AES Encryption for Password Protection,

Complicated Password, HTTPS (SSL) Login Authentication, Basic and digest authentication for

HTTP/HTTPS, Host authentication (MAC address), IP Adress Filter, WSSE and digest

authentication for ONVIF, Control timeout settings, Security audit log, SNMP V2, TLS 1.1, TLS 1.2, TLS 1.2 with updated cipher suites including AES 128 encryption. Brute Force Delay Protection, Signed Firmware, Secure Boot by software check, Secure Boot by hardware check

Remote Connections: 64

I/O Interface

HDMI Output: 1920×1080, 60Hz, 1280×1024, 60Hz, 1280×720, 60Hz, 1024×768, 60Hz VGA Output: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz CVBS Output: 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480

Audio Inputs: 1-ch, RCA $(2.0 \text{ Vp-p}, 1\text{k}\Omega)$ Audio Outputs: 1-ch, RCA $(2.0 \text{ Vp-p}, 1\text{K}\Omega)$

Harddisk bay: 1 x SATA III

8 Channel Video Recorder

GD-RT-BC3008N



I/O Interface

Network Interface: 1x 10, 100, 1000 Base T, TX (RJ-45)

Serial Interface(s): Front panel: 1 × USB 2.0, Rear panel: 1 × USB 2.0, 1 x RS485

Intelligent Functions

Motion Detection: On, Off, Area Setting

Intrusion Detection: Enter and loiter in a pre-defined virtual region

Line Crossing: Cross a pre-defined virtual line

Face Detection: *Human face appears in the image can be detected and trigger event action

(*only if the camera supports this function)

Event Source: Motion, Alarm, Video Loss, System

Event Action: Pop-Up, Relay, E-Mail, FTP, Network, Buzzer, PTZ Preset

Approvals

Regulation: CE, EAC, FCC, RoHS Compliant

Standard: ONVIF (Profile S, Profile G), SDK/API

Environmental

Operating Temperature: $-10^{\circ}\text{C} \sim +55^{\circ}\text{C} \ (+14^{\circ}\text{F} \sim +131^{\circ}\text{F})$ Operating Humidity: $10\% \sim 90\%$, non-condensing

Electrical

Supply Voltage: 12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included

Power Consumption: ≤ 18 W without harddisk

Mechanical

Dimensions: $315 \times 242 \times 48 \text{ mm} (12.4 \times 9.5 \times 1.8 \text{ inch})$

Weight: 1780 g (3.9 lb)

Packaging

Package Dimensions: 485 x 290 x 85 mm (19.1 x 11.4 x 3.3 inch)

Package Weight: 2000 g (4.4 lbs)

Packaging Unit: 8


Bulk Package Dimensions: 723 x 503 x 313 mm (28.5 x 19.8 x 12.3 inch)

Bulk Package Weight: 16500 g (36.4 lbs)

Accessories









GD-CW-VIEWER

GD-CW-FINDER

GD-SW-SCMS

GD-HW-HDD-2TB

GD-RT-BC3008N









GD-HW-HDD-6TB



GD-HW-HDD-8TB



GD-KB-AC1420P

Dimensions

