



Type: PC based NVR - IP - Recorder

Item Code: GD-RX-AP1408R

EAN CODE: 4260573065264

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.


Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Smartphone App



The mobile application was developed to facilitate operators in effectively controlling and managing video systems remotely, at any time. It allows for live image viewing, playback of recorded video data, and receipt of remote notifications.

Features

- C-WERK offers additional benefits from its modular structure and distributed architecture, which enable flexible design of the video systems
- Mobile client support - iPhone, iPad, Android
- Effective hard-disk use results from an in-house file system, which saves space on the hard disk and enhances data security
- Centralized user Management

Specifications GD-RX-AP1408R

Video

Number of cameras:	8 channel (extendable with CAM licences)
--------------------	--

Recording / Playback

Recording Bandwidth:	128 Mbps
Live Viewing:	Customizable interface with personalized layouts and mosaics, emaps, HTML and commands
Recording:	Continuous, motion, or event triggered recording can be scheduled using the calendar object for repetitive action

General

OSD (On Screen Display):	Yes
CPU:	Intel® Core™ i5-10400, 6 Cores, 12 Threads, 12 MB Cache, 2.90 GHz Base Frequency, 4.30 GHz Turbo Frequency
Operating System:	Microsoft® Windows 10 64-bit
Log File Support:	Events, macros, changes, activities per user
RAM:	8 GB
Basic Internal Storage:	240GB SATA SSD M.2
Basic Internal Storage:	6 TB
Storage Device:	Accepts internal server storage as well as NAS, SAN, DAS

Network

Video Compression:	H.264, H.264+, H.265, H.265+ , MJPEG
Streaming:	Two Streams, setting of image resolution, frame rate and data flow

I/O Interface

Video Outputs:	1x DisplayPort, 1x HDMI
Harddisk bay:	3x SATA
Network Interface:	1x RJ45 Gbit LAN
Interfaces:	2x USB 3.1, 2x USB 2.0

Environmental

Operating Temperature:	+5 °C ~ +40 °C (+41°F ~ + 104°F)
------------------------	----------------------------------

Electrical

Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. 400 W

Mechanical

Dimensions:	430 x 88 x 457 mm (2HE / 19")
Weight:	10000 g (22 lb)