



Type: PC based NVR - IP - Recorder

Item Code: GD-RX-AP3464R

EAN CODE: 4260573061686

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.


Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Smartphone App



The mobile application was developed to facilitate operators in effectively controlling and managing video systems remotely, at any time. It allows for live image viewing, playback of recorded video data, and receipt of remote notifications.

Features

- C-WERK offers additional benefits from its modular structure and distributed architecture, which enable flexible design of the video systems
- Mobile client support - iPhone, iPad, Android
- Effective hard-disk use results from an in-house file system, which saves space on the hard disk and enhances data security
- Centralized user Management

Specifications GD-RX-AP3464R

Video

Number of cameras: 64 channel (extendable with CAM licences)

Recording / Playback

Live Viewing: Customizable interface with personalized layouts and mosaics, emaps, HTML and commands

Recording: Continuous, motion, or event triggered recording can be scheduled using the calendar object for repetitive action

General

Max. Storage Capacity: Up to 12 TB capacity for each HDD

OSD (On Screen Display): Yes

CPU: Intel® Core™ i5-13400, 10 Cores, 16 Threads, 20 MB Cache, 2.50 GHz Base Frequency, 4.60 GHz Turbo Frequency

Operating System: Microsoft® Windows 11 Pro 64-bit

Log File Support: Events, macros, changes, activities per user

RAM: 2x 8 GB

Basic Internal Storage: 256 GB SSD M.2

Storage Device: Accepts internal server storage as well as NAS, SAN, DAS

Network

Video Compression: H.264, H.264+, H.265, H.265+ , MJPEG

Streaming: Two Streams, setting of image resolution, frame rate and data flow

I/O Interface

Video Outputs: 1x DisplayPort, 1x HDMI

Harddisk bay: 6 x SATA III

Environmental

Operating Temperature: +5 °C ~ +40 °C (+41°F ~ + 104°F)

Electrical

Supply Voltage: 100 ~ 240 VAC, 50Hz / 60Hz

Power Consumption: Max. 400 W

Mechanical

Dimensions: 430 x 88 x 457 mm (2HE / 19")

Weight: 10000 g (22 lb)