GD-RX-AP3464R











Type: PC based NVR - IP - Recorder

Item Code: GD-RX-AP3464R EAN CODE: 4260573061686

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.

Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.



Smartphone App

The mobile application was developed to facilitate operators in effectively controlling and managing video systems remotely, at any time. It allows for live image viewing, playback of recorded video data, and receipt of remote notifications.

Features

- C-WERK offers additional benefits from it's modular structure and distributed architecture, which enable flexible design of the video systems
- Mobile client support iPhone, iPad, Android

- Effective hard-disk use results from an in-house file system, which saves space on the hard disk and enhances data security
- Centralized user Management

GD-RX-AP3464R



Specifications GD-RX-AP3464R

Video	
Number of cameras:	64 channel (extendable with CAM licences)
Recording / Playback	
Live Viewing:	Customizable interface with personnalized layouts and mosaics, emaps, HTML and commands
Recording:	Continuous, motion, or event triggered recording can be scheduled using the calendar object for repetitive action
General	
Max. Storage Capacity:	Up to 12 TB capacity for each HDD
OSD (On Screen Display):	Yes
CPU:	Intel® Core™ i5-13400, 10 Cores, 16 Threads, 20 MB Cache, 2.50 GHz Base Frequency, 4.60 GHz Turbo Frequency
Operating System:	Microsoft® Windows 11 Pro 64-bit
Log File Support:	Events, macros, changes, activities per user
RAM:	2x 8 GB
Basic Internal Storage:	256 GB SSD M.2
Storage Device:	Accepts internal server storage as well as NAS, SAN, DAS
Network	
Video Compression:	H.264, H.264+, H.265, H.265+ , MJPEG
Streaming:	Two Streams, setting of image resolution, frame rate and data flow
I/O Interface	
Video Outputs:	1x DisplayPort, 1x HDMI
Harddisk bay:	6 x SATA III
Environmental	
Operating Temperature:	+5 °C ~ +40 °C (+41°F~ + 104°F)
Electrical	
Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. 400 W
Mechanical	
Dimensions:	430 x 88 x 457 mm (2HE / 19")
Weight:	10000 g (22 lb)