

Type: Bullet - Thermal Imaging - Camera

Item Code: GD-TI-AP4507T

EAN CODE: 4260573064823

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.


Highlights

Objekt Classification



This technology employs a highly advanced deep learning algorithm that can discern whether the alarm was triggered by a human, a vehicle or some other object.

Deep Learning



Deep Learning is inspired by the complex structure of the human brain. This innovative method allows processing of information and performing corresponding actions based on analysis.

Features

- Reduction of unwanted alarms (false alarms) by classifying target objects using deep learning algorithms. This significantly reduces false alarms generated by objects other than people or vehicles. This makes finding events easier and saves hard drive capacity
- Audio Communication & Alarm Input / Output
- Picture in Picture - Partial image of infrared channel on the full image of optical channel
- Dual Streaming with 1 infrared channel and 1 optical channel
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 30m
- White light flash and audible alarm deterrent function

Specifications GD-TI-AP4507T

Thermal module

Thermal Sensor:	Vanadium Oxide Uncooled Focal Plane Array
Resolution (Thermal):	256 x 192
IFOV:	1.74 mrad
NETD:	< 40 mk (@25° C, F=1.0)
Response Waveband:	8 µm to 14 µm
Detector Pitch:	12 µm
Focal Length (IR):	6.9 mm
Viewing Angle (IR):	24.5° x 18.5° (HxV)
MOD (Min. Object Distance):	1.3 m

Camera

Image Sensor:	1/2.7" progressive Scan CMOS
Video Resolution:	2688 x 1520
Sensitivity Colour:	0.0089Lux @ F1.6 (AGC ON)
Sensitivity B/W:	0.0035 Lux @ F2.25, (AGC ON)
Shutter Speed:	1 ~ 1/100,000 s

Lens

Lens Focal Length:	6.4 mm
Iris F-Number:	F1.6
Field of View:	53° (horizontal), 28° (vertical)

Illuminator

Max. IR Distance:	Up to 30 m
White Light Distance:	Up to 30 m
White LED:	Alarm/ Off

Video

Wide Dynamic Range:	120 dB
Day/Night Switch:	Color, BW, Auto

Audio

Audio Compression:	G722.1/G711ulaw/G711alaw/G726/MP2L2/PCM
--------------------	---

General

Measurement option:	Support 3 temperature measurement rule types, 21 rules (10 points, 10 regions and 1 line)
Object Temperature Range:	- 20°C to 150°C
Accuracy:	± 8°C
DRI Range:	Detection Range, Vehicles 1.4 m x 4.0 m: 881 m Detection Range, Humans 1.8 m x 0.5 m: 287 m Recognition Range, Vehicles 1.4 m x 4.0 m: 220 m Recognition Range, Humans 1.8 m x 0.5 m: 72 m Identification Range, Vehicles 1.4 m x 4.0 m: 110 m Identification Range, Humans 1.8 m x 0.5 m: 36 m
Smart Function Range:	VCA Range, Vehicles 1.4 m x 4.0 m: 145 m VCA Range, Humans 1.8 m x 0.5 m: 55 m Temperature Measurement, Object 1 x 1 m: 117 m Temperature Measurement, Object 0.2 x 0.2 m: 23 m
Accessories included:	Junction box

Network	
Users:	3 Levels: Administrator, Operator and User
Number of Clients:	Up to 20 simultaneously
Video Compression:	H.264, H.265, MJPEG
SD Memory:	Micro SD/SDHC/SDXC card slot with ANR (up to 256G), NAS (Support NFS, SMB/CIFS)
Client software:	C-WERK Viewer, SCMS, IOS App, Android App (SCMS)
Web Browser:	Plug-in required live view: Internet Explorer 11 Non Plug-in live view and service: Chrome 57.0+, Mozilla Firefox 52+
Frame Rate:	Main Stream: Thermal: 25 fps (1280 × 720, 704 × 576, 640 × 512, 320 × 240) Optical: 50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720) Sub-stream: Thermal: 25 fps (704 × 576, 640 × 512, 320 × 240) Optical: 50 Hz: 25 fps (704 × 576, 352 × 288) 60 Hz: 30 fps (704 × 480, 352 × 240)
Network Protocol:	TCP/IP, IPv4/IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, UDP, PPPoE, SNMP
Cyber Security:	3 levels of user management: admin, operator, user, AES Encryption for Password Protection, Complicated Password, HTTPS (SSL) Login Authentication, Basic and digest authentication for HTTP/HTTPS, 802.1X authentication (EAP-TLS), 802.1X authentication (EAP-MD5), Watermark, IP Adress Filter, WSSE and digest authentication for ONVIF, RTP/RTSP over HTTPS, Control timeout settings, Security audit log, SNMP V2, SNMP V3, TLS 1.1, TLS 1.2, TLS 1.2 with updated cipher suites including AES 256 encryption. Brute Force Delay Protection, Signed Firmware, Secure Boot by software check
I/O Interface	
Video Outputs:	1x CVBS (1 Vcc) BNC
Audio Input/Output:	1-ch audio input and 1-ch audio output
Alarm Input/Output:	2, 2
Network Interface:	1x 10, 100 Base T, TX PoE+ (RJ-45)
Serial Interface(s):	1x RS-485
Intelligent Functions	
Intrusion Detection:	Enter and loiter in a pre-defined virtual region
Line Crossing:	Cross a pre-defined virtual line
Region Entrance:	Enter a pre-defined virtual region from the outside place
Region Exiting:	Exit from a pre-defined virtual region
Event Source:	Video tampering, network disconnected, IP address conflicted, HDD full, HDD error, illegal login, motion detection
Event Action:	Recording: Pre-event, post-event memory card and/or network storage. Picture upload: FTP, HTTP and NAS. Trigger E-mail notification: HTTP, ISAPI. Audio alarm, white light alarm, alarm output and notification to C-WERK VMS. Events are depending on schedule settings.
Sound Alarm:	2 types of audible alarm (VCA and Temperature) 2 preset voice alerts (one for each) 6 importable user-defined voice alerts (6 options shared in the two types)
Visual Alarm:	White light alarm with adjustable flashing frequencies
Approvals	
Protection Rating:	IP67 (IEC 60529-2013)
Standard:	ONVIF (Profile S, Profile G), SDK/API

Environmental

Operating Temperature:	-40 °C ~ 65 °C (-40 °F ~ 149 °F)
Humidity:	Less than 95%, non condensing

Electrical

Surge Protection:	TVS 4000V Lightning Protection, Surge Protection and Voltage Transient Protection
Supply Voltage:	12 VDC, 24 VAC, PoE (IEEE 802.3af)
Power Consumption:	Max. 8.2 W

Mechanical

Dimensions:	358 × 114 × 115 mm (14.1 × 4.47 × 4.53 inch)
Weight:	1550 g (3.41 lb)

Packaging

Package Dimensions:	395 x 195 x 158 mm (15.6 x 7.7 x 6.2 inch)
Package Weight:	1900 g (4.2 lbs)

Accessories



GD-BR-AMC03



GD-BR-AML01

Guarantee

All cameras in the “SMART”, “PRO” and “PREMIUM” product lines have an extended warranty period of 5 years on electronic parts, mechanical wear and tear on moving parts is not included. Please note our general delivery terms and conditions.